

HAUTE PERFORMANCE

HIGH PERFORMANCE



Ref. MM220L

6-7 x Ø

Ø	l	l2	d	L	€	Ø	l	l2	d	L	€
0.30	2.0	-	3.00	50	21.00	1.70	12.0	15.0	3.00	50	16.20
0.35	2.25	-	3.00	50	21.00	1.75	12.5	15.5	3.00	50	16.20
0.40	2.5	-	3.00	50	21.00	1.80	13.0	16.0	3.00	50	16.20
0.45	3.0	-	3.00	50	21.00	1.85	13.0	16.0	3.00	50	16.20
0.50	3.5	4.4	3.00	50	16.50	1.90	13.5	17.5	3.00	50	16.20
0.55	4.0	5.0	3.00	50	16.50	1.95	14.0	18.0	3.00	50	16.20
0.60	4.5	5.6	3.00	50	16.50	2.00	14.0	18.0	3.00	50	16.20
0.65	5.0	6.2	3.00	50	16.50	2.05	14.5	18.5	3.00	50	17.10
0.70	5.0	6.2	3.00	50	16.50	2.10	15.0	19.0	3.00	50	17.10
0.75	5.5	6.9	3.00	50	16.50	2.15	15.0	19.0	3.00	50	17.10
0.80	5.6	7.2	3.00	50	16.50	2.20	16.0	20.0	3.00	50	17.10
0.85	6.0	7.6	3.00	50	16.50	2.25	16.0	20.0	3.00	50	17.10
0.90	6.5	8.1	3.00	50	16.50	2.30	16.5	21.0	3.00	50	17.10
0.95	6.7	8.5	3.00	50	16.50	2.35	16.5	21.0	3.00	50	17.10
1.00	7.0	8.8	3.00	50	16.50	2.40	17.0	22.0	3.00	50	17.10
1.05	7.5	9.4	3.00	50	15.75	2.45	17.5	22.5	3.00	50	17.10
1.10	8.0	10.1	3.00	50	15.75	2.50	18.0	23.0	3.00	50	17.10
1.15	8.1	10.4	3.00	50	15.75	2.55	18.0	23.0	3.00	50	17.55
1.20	8.5	11.0	3.00	50	15.75	2.60	18.5	23.5	3.00	50	17.55
1.25	8.9	11.3	3.00	50	15.75	2.65	18.5	23.5	3.00	50	17.55
1.30	9.2	11.7	3.00	50	15.75	2.70	19.0	24.0	3.00	50	17.55
1.35	9.6	12.2	3.00	50	15.75	2.75	19.0	24.0	3.00	50	17.55
1.40	10.0	12.5	3.00	50	15.75	2.80	20.0	25.0	3.00	50	17.55
1.45	10.5	13.0	3.00	50	15.75	2.85	20.0	25.0	3.00	50	17.55
1.50	10.5	13.0	3.00	50	15.75	2.90	21.0	26.0	3.00	50	17.55
1.55	11.0	13.5	3.00	50	16.20	2.95	21.0	26.0	3.00	50	17.55
1.60	11.5	14.0	3.00	50	16.20	3.00	21.0	26.0	3.00	50	17.55
1.65	12.0	15.0	3.00	50	16.20						



$\alpha : 140^\circ$

$z : 2 - 30^\circ$

Tol Ø : h5

Tol d : h5

Carbure-Carbide MG 10% Co

HAUTE PERFORMANCE

HIGH PERFORMANCE



12 x Ø

Ref. MM220XL

Ø	l	l2	d	L	€	Ø	l	l2	d	L	€
0.30	3.6	-	3.00	50	23.40	1.50	18.0	21.6	3.00	50	19.95
0.35	4.2	-	3.00	50	23.40	1.55	18.6	22.3	3.00	60	19.95
0.40	4.8	-	3.00	50	23.40	1.60	19.2	23.0	3.00	60	19.95
0.45	5.4	-	3.00	50	23.40	1.65	19.8	23.7	3.00	60	19.95
0.50	6.0	7.2	3.00	50	18.90	1.70	20.4	24.5	3.00	60	19.95
0.55	6.6	7.9	3.00	50	18.90	1.75	21.0	25.2	3.00	60	19.95
0.60	7.2	8.6	3.00	50	18.90	1.80	21.6	25.9	3.00	60	19.95
0.65	7.8	9.3	3.00	50	18.90	1.85	22.2	26.6	3.00	60	19.95
0.70	8.4	10.1	3.00	50	18.90	1.90	22.8	27.3	3.00	60	19.95
0.75	9.0	10.8	3.00	50	18.90	1.95	23.4	28.1	3.00	60	19.95
0.80	9.6	11.5	3.00	50	18.90	2.00	24.0	28.8	3.00	60	19.95
0.85	10.2	12.2	3.00	50	18.90						
0.90	10.8	13.0	3.00	50	18.90						
0.95	11.4	13.7	3.00	50	18.90						
1.00	12.0	14.4	3.00	50	18.90						
1.05	12.6	15.1	3.00	50	18.15						
1.10	13.2	15.8	3.00	50	18.15						
1.15	13.8	16.5	3.00	50	18.15						
1.20	14.4	17.3	3.00	50	18.15						
1.25	15.0	18.0	3.00	50	18.15						
1.30	15.6	18.7	3.00	50	18.15						
1.35	16.2	19.4	3.00	50	18.15						
1.40	16.8	20.1	3.00	50	18.15						
1.45	17.4	20.9	3.00	50	18.15						



α : 140°
 z : 2 - 30°
 Tol Ø : h5
 Tol d : h5
 Carbure-Carbide MG 10% Co